

**WHAT IS CLAIMED IS:**

- 1 1. A thermal transfer system, comprising:  
2 a container for receiving a medium;  
3 a structure positioned in the container such that the structure segments the  
4 container into a plurality of compartments wherein a distal end of the structure is in  
5 close proximity to an interior surface of the container to allow formation of a thermal  
6 transfer bridge that conducts heat into or out of the medium.
- 1 2. A thermal transfer system as in claim 1 including:  
2 a heating or cooling device coupled to and provides heating or cooling of the  
3 container.
- 1 3. A thermal transfer system as in claim 1 including:  
2 a heating or cooling device coupled to and provides heating or cooling of the  
3 structure.
- 1 4. A thermal transfer system as in claim 1 including:  
2 a heating or cooling device coupled to and provides heating or cooling of the  
3 container and the structure.
- 1 5. A thermal transfer system as in claim 1 including:  
2 a plurality of structures in the container.
- 1 6. A thermal transfer system as in claim 1, including:  
2 a removable liner configured to cover at least a portion of the structure.
- 1 7. A thermal transfer system as in claim 1 wherein:  
2 a volume of the container is in the range from substantially 1 liter to 250  
3 liters.
- 1 8. A thermal transfer system as in claim 1 wherein:  
2 a volume of the container is in the range from substantially 250 liter to  
3 10,000 liters.
- 1 9. A thermal transfer system as in claim 1 wherein:

2 the distal end of the structure contacts at least a portion of the interior surface  
3 of the container.

1 10. A thermal transfer system as in claim 1 wherein:  
2 a distance between the distal end of the structure and the interior surface of  
3 the container is a non-contacting distance not greater than one inch.

1 11. A thermal transfer system as in claim 1 wherein:  
2 the container includes a jacket defining an interstitial space positioned  
3 between the jacket and a wall of the container for receiving a flow of a heat exchange  
4 fluid, the jacket further including a plurality of spiral baffles for enhancing thermal  
5 exchange between the heat exchange fluid and the container.

1 12. A thermal transfer system as in claim 1 wherein:  
2 a heat exchange fluid flows within the structure.

1 13. A thermal transfer system as in claim 12 wherein:  
2 an interior portion of the structure has baffles.

1 14. A thermal transfer system as in claim 13 wherein:  
2 the structure is configured to maximize an area of a surface of the structure  
3 that is in contact with the medium.

1 15. A thermal transfer system as in claim 12 wherein:  
2 a heat exchange extension is at least partially coupled to the structure.

1 16. A thermal transfer system as in claim 1 wherein:  
2 the medium is substantially uniformly heated or cooled.

1 17. A thermal transfer system as in claim 1 wherein:  
2 the medium is heated or cooled in substantially one direction relative to the  
3 structure.

1 18. A thermal transfer system as in claim 1 wherein:  
2 the structure is positioned to induce a thermal gradient in the medium such  
3 that the thermal gradient is in a predetermined direction.

- 1 19. A thermal transfer system as in claim 1 wherein:  
2 the medium is heated or cooled in a predetermined direction.
- 1 20. A thermal transfer system as in claim 1 wherein:  
2 the medium is heated or cooled such that the thermal gradient is in a  
3 predetermined direction.
- 1 21. A thermal transfer system as in claim 1 wherein:  
2 the medium is heated or cooled at a predetermined rate.
- 1 22. A thermal transfer system as in claim 1 wherein:  
2 the medium is heated or cooled such that the thermal gradient is in a  
3 predetermined direction and the heating or cooling occurs at a predetermined rate.
- 1 23. A thermal transfer system as in claim 1 wherein:  
2 the medium is a biopharmaceutical product.
- 1 24. A thermal transfer system as in claim 1 wherein:  
2 the container has a nonporous bottom.
- 1 25. A thermal transfer system as in claim 1 wherein:  
2 the container has nonporous walls.
- 1 26. A thermal transfer system as in claim 1 wherein:  
2 the container has a top.
- 1 27. A thermal transfer system as in claim 1 wherein:  
2 the container has a nonporous top.
- 1 28. A thermal transfer system as in claim 1 including:  
2 a distal portion of the structure configured to improve thermal transport of  
3 the thermal transfer bridge.
- 1 29. A thermal transfer system as in claim 1 wherein:  
2 the medium includes proteins.





- 1 47. A thermal transfer system as in claim 30 wherein:  
2 a heat exchange fluid flows into the heat exchange member from a heat  
3 exchange supply line.
- 1 48. A thermal transfer system as in claim 38 wherein:  
2 the heat exchange fluid flows does not flow through the distal end of the heat  
3 exchange member.
- 1 49. A thermal transfer system as in claim 30 wherein:  
2 a distance between the distal end of the heat exchange member and the  
3 interior surface of the container is a non-contacting distance not greater than one  
4 inch.
- 1 50. A thermal transfer system as in claim 30 wherein:  
2 the medium is substantially uniformly heated or cooled.
- 1 51. A thermal transfer system as in claim 30 wherein:  
2 the medium is heated or cooled in substantially one direction relative to the  
3 structure.
- 1 52. A thermal transfer system as in claim 30 wherein:  
2 the medium is heated or cooled at a predetermined rate.
- 1 53. A thermal transfer system as in claim 30 wherein:  
2 the medium is heated or cooled such that the thermal gradient is in a  
3 predetermined direction and the heating or cooling occurs at a predetermined rate.
- 1 54. A thermal transfer system as in claim 30 wherein:  
2 the medium is a biopharmaceutical product.
- 1 55. A thermal transfer system as in claim 30 wherein:  
2 the medium includes proteins.